PVC





PRODUCT DESCRIPTION

PVC Packaging tape is made with an unplastified assorted coloured PVC film backing and a natural rubber and hydrocarbon resins white adhesive. This printable carton sealing coloured PVC tape is perfect for manual dispenser application, offering excellent adhesion even in recycled cartons. With excellent tack and long-lasting adhesion, this tape also features silent unwinding with no noise. It is printable with vinyl inks and is ideal for storage in extreme temperature conditions and high moisture environments once applied.

PHYSICAL PROPERTIES

Backing: PVC film
Adhesive: Natural rubber
Total Thickness: 55 micron
Peel Adhesion: 2,4 N/cm
Tensile Strength: 53 N/cm

Elongation at Break: 60%

Application Temperature: 10°C to 45°C Service Temperature: -25°C to 65°C

STANDARD WIDTHS

9 mm,12 mm, 24 mm, 48 mm Custom widths also available

STANDARD LENGTHS

66 metres

AVAILABLE COLOURS

Blue, green, orange, purple, red, white & yellow



RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.

The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.