

DC-4623MF

Lowry
The Tape Specialists

DOUBLE COATED HEAVY DUTY REINFORCED TRANSFER TAPE

PRODUCT DESCRIPTION

This heavy duty scrim tape has a thick polyester reinforced transfer tape (PES/PVA Scrim) with an aggressive, modified solvent free water based acrylic adhesive. The adhesive system is extremely aggressive, and will bond well to nearly all materials; even to difficult surfaces like foam, PE and PP films. It has good temperature, UV, aging, and water vapor resistance. Used for permanent bonding of plastic, metal and wood (P.M.W.) surfaces. APEO/APE Free. Primarily designed for use in bonding carpet and plastic baseboard molding to walls, ceilings, modular units, etc

PHYSICAL PROPERTIES

Adhesive:	Solvent free water based acrylic adhesive
Release Liner:	90gsm Gold glassine paper
Total Thickness:	9.1 mils
Adhesion:	120 oz/in
Holding Power:	≥ 16 hours
Temperature Resistance:	-40°F to 194°F (-40°C to 90°C)
Core I.D.:	3" neutral core

STANDARD WIDTHS

6 mm, 12 mm, 24 mm, 36 mm, 48 mm, 72, mm, 96 mm
Custom widths available

STANDARD LENGTHS

55 yards (50 metres)

RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.