



PVC FILM PACKAGING TAPE

PRODUCT DESCRIPTION

PVC Packaging tape is specifically designed for use as packaging tape on commercial cartons. It provides reliable and secure sealing for large cartons and plastic containers. With high tensile and adhesion strength, this tape is moisture resistant and can withstand diluted acids and alkalis. It is heat resistant for short periods up to about 70°C and can also withstand low temperatures down to about -20°C after application at room temperature.

PHYSICAL PROPERTIES

Backing:	Rigid PVC film
Adhesive:	Natural rubber
Breaking Load:	Minimum 90 N/25 mm Minimum 36 N/cm
Thickness:	0.052 mm \pm 10%
Adhesion Strength:	500 \pm 150 cN/25 mm 2,0 \pm 0,6 N/cm
Core Diameter:	76 mm

STANDARD WIDTHS

9 mm, 12 mm, 24 mm, 48 mm
Custom widths also available

STANDARD LENGTHS

66 metres

RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.