

425 | 426 | 4250 | 4260

HOT MELT



UTILITY GRADE CARTON SEALING TAPE



PRODUCT DESCRIPTION

This Utility Grade packaging tape is primarily used for carton sealing, splicing, bundling, and other lightweight packaging applications. This product has a conformable film backing coupled with a consistent pressure sensitive hot melt adhesive coating.

PERFORMANCE FEATURES

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Good edge tear and split resistance.
- Aggressive high tack adhesive with excellent holding powers

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Vibac Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

TECHNICAL SPECIFICATIONS

Color:	Clear <input type="radio"/> Tan <input type="radio"/>
Backing (mils/mm): BOPP	0.96 / 0.024
Adhesive:	Synthetic Rubber and Resins
Total Thickness (mils/mm):	1.54 / 0.040
Adhesion to Steel (oz/in. - N/100mm):	44 / 48
Tensile Strength (lbs/in. - N/100mm):	22 / 385
Elongation at Break:	165%
Service Temp. - Min / Max:	30°F (-2°C) / 140°F (60°C)
Application Temp. - Min / Max:	54°F (12°C) / 110°F (43°C)
Available Widths:	48mm, 72mm
Available Lengths (hand): 50m, 66m, 100m, 132m, 150m, 200m	
Available Lengths (machine):	914m, 1371m, 1828m

