

# SW132

**Lowry**  
The Tape Specialists



## DOUBLE COATED POLYETHYLENE FOAM TAPE

### PRODUCT DESCRIPTION

Double coated polyethylene foam tape with a pressure sensitive acrylic adhesive. It designed for fast and easy to use permanent bonding with high strength and long-term durability. Ideally used for low-surface energy substrates such as many plastics, aluminum and glass. This product is commonly used for window glazing applications.

### PHYSICAL PROPERTIES

Backing:	Polyethylene Foam (67kg/CBM)
Colour:	White
Adhesive:	Acrylic Solvent
Release Liner:	PE Liner
Thickness:	1/32" (0.8 mm)
Initial Tack:	≥ 30 N / 25.4 mm
Holding Power:	≥ 50 hours
Heat Resistance:	-20°C ~ + 80°C
Core I.D.:	3" (76mm±1)

### STANDARD WIDTHS

Custom widths available

### STANDARD LENGTHS

216 feet (66 metres)

### RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.