



Product Specification 6525-08

Taconic 6525-08 is a plasma spray masking tape constructed from silicone coated fiberglass complete with silicone adhesive. The tape is a reliable maskant to protect against heat and abrasion associated with surface prep blasting, electric arc spray, combustion flame spray, and plasma spray coatings. The tape is designed to release cleanly from metal surfaces leaving no adhesive residue. This tape comes with a yellow dimpled PVC release liner. Maximum width is 38" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		SILICONE		
Substrate Type		LSR E-GLASS		
Total Weight of Substrate		N/A		
% Coating of Substrate		N/A		
Substrate Thickness	inch	0.008		ASTM D3652
Adhesive Thickness	inch	0.003		ASTM D3652
Total Product Thickness	inch	0.011		ASTM D3652
Adhesive Strength	ozs	50	Typical	ASTM D3330 METHOD A
		40	Minimum	
Adhesive Strength from Backing	ozs	20		ASTM D3330 METHOD B
Adhesive Shelf Life	Months	12	From DOM	
Operating Temperature	°Fahrenheit	-100° to +500°		

Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
 Petersburg, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
 La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
 Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
 or email info@taconic-ipd.com

