

730 | 731 | 7300 | 7301

HOT MELT



HIGH PERFORMANCE CARTON SEALING TAPE



PRODUCT DESCRIPTION

This High Performance packaging tape was designed for carton sealing, splicing, bundling, and other extra heavy packaging applications. This product offers superior adhesive power for bulky and heavy boxes.

PERFORMANCE FEATURES

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Good edge tear and split resistance.
- Aggressive high tack adhesive with excellent holding powers

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Vibac Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

TECHNICAL SPECIFICATIONS

| | |
|--|--|
| Color: | Clear <input type="checkbox"/> Tan <input checked="" type="checkbox"/> |
| Backing (mils/mm): BOPP | 1.57 / 0.040 |
| Adhesive: | Synthetic Rubber and Resins |
| Total Thickness (mils/mm): | 2.44 / 0.062 |
| Adhesion to Steel (oz/in. - N/100mm): | 56 / 60 |
| Tensile Strength (lbs/in. - N/100mm): | 36 / 630 |
| Elongation at Break: | 200% |
| Service Temperature - Min / Max: | 30°F (-2°C) / 140°F (60°C) |
| Application Temperature - Min / Max: | 50°F (10°C) / 110°F (43°C) |
| Available Widths: | 36mm, 48mm, 72mm, 96mm, 144mm |
| Available Lengths (hand): | 50m, 55m, 100m |
| Available Lengths (machine): | 914m |

