


## **Professional Grade Duct Tape**



Backing

Adhesive

Backing: PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Silver, Black, White, Blue, Brown, Green

OD, Red, Yellow

Rajo VOCS in

**Specifications:** Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

## **Applications**

- Hanging and patching polyethylene sheeting
- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing environments
- Seaming and securing underlayment materials
- Sealing polyethylene waste disposal bags
- Color coding
- General repair
- Bundling, patching, and mending

## Features Benefits

•	PE-Coated Cloth Backing		Excellent balance of tensile strength and tearability Available in a wide range of colors
•	Natural Rubber Adhesive		Aggressive adhesion to rough surfaces Superior holding power for hanging applications
•	Low VOC Content	•	Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

**Typical Test Values** 

- <b>, p</b>						
	Standard UOM	Metric UOM	Test Method			
Total Thickness	11.0 mils	0.279 mm	ASTM D-1000			
Adhesion to Steel	80 oz/in	8.75 N/cm	PSTC-101			
Tensile Strength	26 lb/in	45.53 N/cm	ASTM D-1000			
Operating Temperature	40 to 200 °F	4 to 93 °C				
Elongation	21%		ASTM D-1000			
Smoke Developed	5		UL 723			
Flame Spread	5		UL 723			
VOC Content	<1 g/L					

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

