

5000

Lowry

The Tape Specialists



POLYPROPYLENE PACKAGING TAPE

PRODUCT DESCRIPTION

A heavy-duty carton sealing tape that is perfect for both manual dispensers and automated applications. It has excellent adhesion, even in recycled cartons, and boasts excellent tack for a secure seal. With long-lasting adhesion, this tape is ideal for storage in extreme temperature conditions and high moisture environments once applied.

PHYSICAL PROPERTIES

Backing:	Clear BOPP film
Adhesive:	Natural rubber and hydrocarbon resins
Total Thickness:	50 micron
Peel Adhesion:	1,9 N/cm
Tensile Strength:	55 N/cm
Elongation at Break:	100%
Application Temperature:	2°C to 45°C
Service Temperature:	-25°C to 65°C

STANDARD WIDTHS

48 mm

STANDARD LENGTHS

66 metres

RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.