

# 7970

# Lowry

The Tape Specialists



## DOUBLE COATED PVC TAPE

### PRODUCT DESCRIPTION

This double coated PVC tape contains a gold siliconized paper release liner and an acrylic solvent adhesive. Extremely aggressive adhesive bonds to a wide range of high and low surface energy substrates, including smooth, rough, and textured surfaces.

Excellent temperature, UV, aging, and water vapour resistance. Ideal for mounting heavy signs, POS displays and large format graphics. Used for secure attachment of extruded plastic profiles in furniture and general industries.

### PHYSICAL PROPERTIES

Backing:	Ivory PVC 100 micron
Adhesive:	Acrylic Solvent
Release Liner:	Gold Glassine 85 gms
Total Thickness:	245±10 micron (without liner)
180°C Peel Strength to Steel Plate:	≥ 1.8 kg/25 mm (18N/25 mm)
Initial Tack Steel Ball 14#:	≤ 55 mm
Holding Power:	≥ 48 hours
Core I.D.:	3" (76mm±1)

### STANDARD WIDTHS

6 mm, 12 mm, 24 mm, 36 mm, 48 mm, 72, mm, 96 mm  
Custom widths also available

### STANDARD LENGTHS

50 metres (55 yards)

### RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.